

YORK® Single Piece Air Handlers

JHET Two-Stage Air Handler
JHVT Variable-Speed Air Handler

1.5-5 ton



Streamlined design, efficient performance, exceptional reliability

YORK® air handlers have been completely redesigned, raising the bar on quality with a higher level of efficiency and operational performance. By changing our traditional coil design, we've ensured homeowners and contractors alike can quickly and easily improve their home comfort system performance.

Next-generation design optimizes performance and efficiency

- Next-generation, high-efficiency blower design delivers improved efficiency.
- A maximum 21" depth, smooth sides and a rigid case construction make installation easier in tight spaces.
- MaxAlloy™ coils made with corrosion-resistant, high-quality aluminum provide lasting performance, efficiency and reliability.
- New, even-flow coil distributor design for improved and balanced refrigerant flow and even coil circuit performance.
- Lock-in, single-piece insulation reduces air leaks.
- Communicating capable as part of a complete YORK® system.



VISIT [YORK.COM](https://www.york.com) FOR MORE INFORMATION

 YORK®

Proven construction

1. Rigid case construction and interior bracing provide solid structural support for all applications.
2. Thermoset drain pan is corrosion- and UV-resistant with a positive slope for drainage.
3. Case doesn't have any protruding screw heads, limiting scratches or other property damage during installation.

Advanced comfort

4. Improved blower uses up to 10% less energy.
5. MaxAlloy™ coils are built to deliver lasting performance, efficiency and reliability.
6. Next-generation "A" coil design for improved efficiency.
7. Achieves 2% or less total airflow leakage rate at duct leakage test conditions in positive and negative pressure for system airflow verification.

Easier installation and servicing

8. Multiposition design for up-flow, down-flow and horizontal applications.
9. New 8HK assortment of plug-and-play electric heat kits for all heating needs.
10. Compact, 21-inch casing depth allows for ease of access in attics and applications where space is limited.
11. Integrated duct flange is part of the casing for faster installation.
12. Factory-installed TXV with nonbraze, bolt-on connectors make installation easy.
13. Toolless filter access.





Image: JHET air handler

Two options for differing home comfort needs

Fixed-speed vs. variable-speed motors

Both the standard ECM fixed-speed and variable-speed options and their ability to control airflow can be thought of in the same way as staged and modulating heating and cooling. Standard ECM fixed-speed motors are two-stage and can operate in a low/med/high fashion. Variable-speed motors, or premium ECM motors, match operation to the exact speed needed, consuming less energy over time and reducing noise levels. This provides a more comfortable space and more efficient operation.



Industry-leading warranties



*All warranties require online registration within 90 days of installation. Otherwise, warranties revert as follows:
10-year Parts Limited Warranty –
5-year Parts Limited Warranty.



We focus on quality, and quality starts with our two-year parts warranty on all genuine YORK® parts. Each genuine part is engineered, built to specification and factory-tested for reliable performance with all YORK® equipment.



Since 1909, this seal has signified that a product has been tested and approved by the Good Housekeeping Research Institute and is guaranteed by Good Housekeeping magazine's trusted Consumer Policy.